

WIND AND EARTHQUAKE LOAD ANALYSIS OF INDUSTRIAL STEEL STRUCTURE USING BRACING AND DAMPER

S.Vijay Muragan¹. G.Naveen Kumar²

^{1, 2}, Assistant Professor, Dept of CIVIL, SVS Group of Institutions, Hanamkonda, Warangal, T.S, India

ABSTRACT:

According to recent trends in earthquakes around the world, it is evident that there is a really high risk of earthquake, necessitating the construction of earthquake-resistant structures. High buildings are vulnerable to both wind and earthquake loads. There are many ways to endure these lateral loads for the purpose of increasing stiffness and reducing lateral variation, including base seclusion, development of hollow foundations, tuned mass dampers, straight bands, and bracing. Bracing is one of the best methods to resist these kinds of loads out of all of these applications. Both concentrically and eccentrically can be used for supporting. The cross bracings are one of the supporting types that are typically used. Bracings are incredibly effective in overcoming flexible seismic waves. This is used to strengthen the structure by increasing its stiffness and variation capacity while minimising side displacement. You can employ a variety of bracings, including X, V, and inverted V types. Research has been done to determine whether the addition of different bracing systems affects how quickly a structure reacts to side loading. By positioning various bracing systems at various locations, a G + 20 building framework of strategic location 10.5 m X 9 m is examined under seismic load in area IV in this study. The feedback range method is used to do the analysis in ETABS. Inverted V, V, and X bracing systems are the bracing systems that are taken into account. These bracings are positioned at the structure's interior and exterior bays. Storey variations, storey wanders, storey shears, as well as reversing moments are examined from the assessment of the buildings with varied bracing. For the lot combination (1.2 DL + 1.2 LL + 1.2 EQ X), these results are evaluated. A structure typically undergoes lateral and tensional displacement as a result of the influence of seismic loading. Any sort of supporting system increases the system's overall rigidity and thereby serves as a control mechanism for the structure's lateral and tensional motion.

Key words: upright loading, X loads, Cross supporting, and X supporting.

1. INTRODUCTION:

Earthquakes are a common occurrence that is caused by movement in the earth's crust, and they claim the lives of hundreds of people every year in various parts of the world. These significant numbers of sources are primarily due to building collapse or issues. Lateral instability has always been a major issue, especially in regions with a high earthquake risk. Concentric, eccentric, and knee bracing techniques have all been used for many years, and they all effectively limit lateral deviations. The centres of mass and strength do not synchronise when an eccentric loading is present in a building's structural system. As a result, the framework reacts in a direction perpendicular to the applied force or tensional force. Being the most harmful effect on a building, torsion requires attention. In constructions based on lateral tonnes, such as wind and seismic pressure, a supported structure is a structural system that is often utilised. Typically, structural steel is used for the members in a supported structure because it performs well in both tension and compression. Supporting is a very effective and economical way to strengthen the mounted structures from side to side. Supporting systems are extremely effective for current framework, where poor lateral stiffness is the main problem, as they allow for a significant increase in stiffness with only a small weight

increase. Bracing is effective because it provides rigidity and resistance to horizontal shear while working in axial tension, requiring minimal participant size. As a result, the supporting system reduces the tensional activity and side motion of the frames under seismic loading. Bracings are offered to minimise side displacement significantly and increase the tightness and stability of the framework under side loading. Concentric bracings increase the framework's lateral rigidity and often reduce side drift. Increased stiffness could cause it to draw in more of the inertia pressure produced by an earthquake. Let's start by noting that when bracings reduce shear stresses and bending moments in columns, axial compression in the columns to which they are attached increases. Eccentric bracings reduce the side tightness of the system and increase the system's ability to dissipate energy. The side tightness of the system depends on the flexural tightness of the light beams in the eccentric link of the bracing to the beams of light. The lateral lots are brought by the bracing system, while the upright lots are brought by the light beam and the columns that form the framework. However, the placement of braces can be a pain because they might alter the appearance of the façade and the location of apertures. In response, structures using modern or post-modernist architectural styles have actually

revealed support as an internal or exterior stylistic function.

2. SURVEY OF LITERARY WORKS:

H. B. Patel (2017), For G +10 constructions such as the Minute Standing Up to Structure (MRF), the R.C.C. structure with V bracing (VBF), and the R.C.C. building with X bracing, they looked at base shear and lateral variation (XBF). The frameworks were examined for Seismic Zone II using ETABS. The base shear was discovered to be highest in XBF and also most reasonably priced in MRF. However, the displacement was discovered for every level of every structure, and it was discovered that Variation was largest in MRF and that it was much decreased in XBF and VBF. As a result of its increased tightness and 61.6% lower lateral variation, XBF is the optimum structure in terms of safety and security, according to these findings.

Nissan, D. E. (2017), He looked at how steel structures behaved during earthquakes both with and without various kinds of supporting systems. Additionally, they provide a comparison of steel frames supported by various technologies under seismic loads. The analysis takes into account the composition of angled supporting, X supporting, Chevron bracing, and V bracing. In this research work, they use pushover analysis to analyse the

capacity curves, base shear, and plasticization of 30 high rise 2-D steel structural frames. They examine the time history of storey displacement, drift proportion, worldwide damages index, and roof covering displacement using time background evaluation. The study explains the improvement in seismic resistance, the efficient decrease of drift, and the similarity of the pushover analysis and temporal backdrop evaluation results.

Gandhi Boundary N. (2017), they created a G + 14 R.C. structure design and tested it using the ETABS seismic zone V programme. They discovered the many aspects of lateral displacement for various structural issues, such as supported frames using cross bracing and V supporting for different heights in a structure at Seismic Zone V. As the Base Shear for X Supporting was significantly more than without bracing, the decision was decided. However, the Floor Displacement was the most affordable option for the X bracing. Additionally, compared to X, V, or without bracings, the Floor Drift was lowest with Inverted V bracing. As a result of these findings, it was determined that X bracing is the best supporting method for the G + 14 R.C building.

Hymavathi G (2015), A G +20 48 x 44 m steel structure that was also to be examined on Staid

was planned for Visakhapatnam. Interior panels of the pro were not braced, but X bracings were provided for the exterior panels. Both Earthquake Zone II and Earthquake Zone V were studied for this framework. The tonnes used in this were based on IS 875:1984, IS 1893:2002, and IS 800:2007. Axial pressure and nodal variation were discovered for the load combinations of "dead tonnes + live loads + wind tonnes" and "dead tonnes + live loads + earthquake tonnes." In both Zone II and Zone V, it was found that the axial force in supported columns was significantly less than that in unraced columns. In comparison to an unraced structure, the Nodal variation for wind and earthquake lots was significantly lower in the braced framework.

Expert Bole (2015), Using the ETABS software, he examined the G +12 R.C structure under seismic circumstances. The building was determined to be in seismic zone III and also evaluated in accordance with IS 1893:2002 using several types of steel and concrete bracing, including angled supporting, V bracing, combine V bracing, K bracing, and X supporting. The bracings were supplied in two different ways: on all four sides of the building, and on just two parallel sides. Results were recorded, and it was concluded that by tightening the structure and enhancing base shear, X bracing is most

successful in reducing side drift and strengthening the framework.

3. MATERIALS AND PROCEDURE

To ensure that sufficient vertical and side toughness and rigidity are reached to satisfy the architectural performance and acceptance deformation degrees recommended in the controlling building ordinance, all buildings are constructed for the combined effects of gravity tonnes and seismic tonnes. Due to the primary security measure used in the style specification, many structures tend to efficiently guard against upright drinking. In constructions with long periods, those requiring security for design, or those undergoing an overall stability examination, upright acceleration should also be taken into account.

In general, many earthquake code arrangements imply that the buildings must be able to withstand:

- A small earthquake that caused no harm.
- Moderate earthquake that caused significant non-structural damage but little structural damage.
- A major earthquake that causes some structural and non-structural damage but no collapse.

- The addition of some structural parts is likely to cause the framework to undergo a significant amount of deformation.

Seismic codes are unique to a particular region or nation. The main code that offered a summary for the computation of seismic style pressure in India is 1893:2002 (part-1). This pressure is determined by the structure's mass and seismic coefficient, which in turn depends on other factors like the importance of the structure, the seismic zone in which it is located, its tightness, the soil on which it rests, and also its ductility. The evaluation of seismic tonnes on various frames and buildings is covered in IS 1893:2002 (part-1). The calculation of base shear and its distribution across height are the entire fixation. The evaluation can be done based on external action, how the chosen structural mode behaves as well as how the chosen framework or architectural materials behave. The majority of the column and the walls above and below the flooring are all handled as separate systems with concentrated mass at floor levels. Additionally, it also complies with the appropriate of live loads at this floor.




Figure 3.1 Plan of the building




Figure 3.2 Elevation and 3D view of the building with inverted V bracings at centre bay.




Figure 3.3 Elevation and 3D view of the building with inverted V bracings at outer bays




Figure 3.4 Elevation and 3D view of the building with V bracings at centre bay




Figure 3.5 Elevation and 3D view of the building with V bracings at outer bays




Figure 3.6 Elevation and 3D view of the building with X bracings at centre bay




Figure 3.7 Elevation and 3D view of the building with X bracings at outer bays




Fig.3.8. Maximum storey overturning moments of a building with X bracings at outer bays.

4. CONCLUSION

When X bracings are provided for the structure at the outer bays, the maximum floor variation in the X-direction is increased. Storey displacements of the structure with X bracings at the outside bays are 10% higher than the building with upside-down V and V bracings at the external and also centre bays.

When X bracings are provided at facility bays for the building, the ideal floor displacement in the Y direction is higher. Storey variations of the structure's inverted V and V bracings at the centre bays are 5% and 12% less than the structure with X bracings at the centre bays specifically.

The floor wanders of the buildings with upside-down V, V, and X bracings are nearly identical in the X-direction. The ideal storey drift, which happened in upside-down V bracings installed at facility bays, is 0.002474.

The building has larger Y-direction story drifts and X-bracings at the exterior bays; the value is 0.000463. Buildings with inverted V and V bracings placed at centre bays have storey drifts that are 46% and 28% lower, respectively, than buildings with X-bracings placed at exterior bays.

The floor shears of the buildings with inverted V, V, and X bracings in the X-direction are almost identical. The strongest storey shear, 362.6566 KN, occurred in external bays with X bracings.

Buildings with inverted V, V, and also X bracings reverse in approximately identical amounts of time. The outer bays' X bracings, where the greatest reverse moment of 301729.6234 KN-m occurred, were responsible.

Buildings in the Y direction with reversed V, V, and X bracings have rescinding times that are quite similar. The external bays' X bracings, where the maximum rescinding moment of 275265.9902 KN-m occurred, were responsible.

The evaluation's findings lead us to the conclusion that a structure with inverted V bracings positioned at outer bays is significantly more reliable to seismic results than a structure with other bracings put at various locations.

Compared to structural frameworks without bracing, supported structural frames are more robust to side loads.

Any sort of bracing system increases the overall tightness of the system and acts as a control mechanism for the structure's lateral and tensional movement.

5. REFERENCES

1. Rafael Isabella, Stephen Mahan, Chino Chang (April 2003), "Seismic demands on steel braced framed buildings with buckling restrained braces", Engineering Journal Science Direct, Elsevier, Volume 25, Issue 5, pp. 655–666.
2. Die Eden Nissan, Ali Khalid Hussein, Abbas Haran Mohammed (2017), "Comparative response assessment of steel frames with different bracing systems under seismic effect", Structures, Elsevier, Volume 11, Issue 1, pp. 229–242.
3. Neumann Mohammed, Islam Nauru (December 2013), "Behavior of multistory RCC structure with different type of bracing system (A Software Approach)", International Journal of Innovative Research in Science, Engineering and Technology, ISSN: 2319-8753, Volume 2, Issue 12, pp. 7468–7478.

4. Bharat Patel, Roan Mali, Prataprao Jadhav, G Mohan Ganesh (March 2017), "Seismic Behavior of different bracing systems in high rise RCC buildings", International Journal of Civil Engineering and Technology (IJCET), Volume 8, Issue 3, pp. 973–981, Article ID: IJCET_08_03_098.
5. G Hymavathi, B Kranthi Kumar, N Vidya Sagar Lal (November 2015), "Performance of high rise steel building with and without bracings", International Journal of Engineering Research and Applications, Volume 5, Issue 11, (Part 4), pp. 103–114, ISSN: 2248-9622.
6. Prof. Bhosle Ashwini Tanaji, Prof. Shaikh AN (Sep.–Oct. 2015), "Analysis of Reinforced Concrete Building with Different Arrangement of Concrete and Steel Bracing system", IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE), Volume 12, Issue 5, Ver. V, pp. 08–12, e-ISSN: 2278-1684, p-ISSN: 2320-334X.
7. Soundarya N Gandhi, YP Pawar, Dr. CP Pise, SS Kadam, CM Deshmukh, DD Mohite (September 2017), "Strengthening of Reinforced Concrete and Steel Structure by using Steel Bracing System", International Research Journal of Engineering and Technology (IRJET), Volume 4, Issue9, pp. 517–522, e-ISSN: 2395-0056, p-ISSN: 2395-0072.
8. Dhanaraj M Patil, Keshav K Sangle (2015), "Seismic Behavior of Different Bracing Systems in High Rise 2D Steel Buildings", Science Direct, Structures, Volume 3, pp. 282–305.
9. Kulkarni JG, Kore PN (2013), "Seismic response of reinforced concrete braced frames", IJERA, Volume 3, Issue 4, pp. 1047–1053.
10. O Alshamrani, GG Schierle, K Galal, and D Vergun (2009), "Optimal bracing type and position to minimize lateral drift in high-rise buildings", WIT Transactions on The Built Environment, Volume 106, pp. 155–166, ISSN 1743-3509.